

APPLICATION FOR U.S. PATENT
TRANSMITTAL FORM

Box Patent Application
THE COMMISSIONER OF PATENTS
AND TRADEMARKS
Washington, D.C. 20231

Attorney Docket No.:
062891.0320

Sir:

Transmitted herewith for filing is the patent application
of:

Inventors: Shrinivas (nmi) Lohia

For: SYSTEM FOR COMMUNICATING MANAGEMENT INFORMATION
AND METHOD OF OPERATION


Enclosed are: 2 Sheets of Formal Drawings

FEE CALCULATION					FEE
	Number		Number Extra	Rate	Basic Fee \$760.00
Total Claims:	20	- 20 =	0	X \$18 =	\$.00
Independent Claims	3	- 3 =	0	X \$78 =	\$.00
TOTAL FILING FEE =					\$760.00

Enclosed is a check in the amount of \$760.00. Please charge
any additional fees or credit any overpayment to Deposit Account
No. 02-0384 of BAKER & BOTTS, L.L.P.

BAKER & BOTTS, L.L.P.
Attorneys for Applicant

November 9, 1999
Date


Samir A. Bhavsar
Registration No. 41,617

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Shriniwas (nmi) Lohia
Date Filed: November 9, 1999
Title: SYSTEM FOR COMMUNICATING
MANAGEMENT INFORMATION AND METHOD
OF OPERATION

BOX PATENT APPLICATION

Honorable Assistant Commissioner
For Patents
Washington, D.C. 20231

Dear Sir:

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that the attached Patent Application, Declaration and Power of Attorney, 2 sheets of formal Drawings, Assignment, Assignment Cover Sheet, a check in the amount of \$40.00 to cover the assignment recording fee, Fee Transmittal, a check in the amount of \$760.00 to cover the application filing fee, and this Certificate of Mailing are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on this 9th day of November, 1999 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.



Willie Jiles

Express Mail Receipt
No. EM 082636754 US
Attorney's Docket:
062891.0320

1

SYSTEM FOR COMMUNICATING MANAGEMENT
INFORMATION AND METHOD OF OPERATION

TECHNICAL FIELD OF THE INVENTION

This invention relates in general to data communication, and more particularly to a system for communicating management information.

5

062891.0320

Network devices are generally arranged in a chassis or housing at a particular location in a communication system. Each network device arranged in a particular chassis may be configured, initialized, or otherwise managed using consoles external to the chassis. A drawback to prior systems is that each network device in a chassis requires a corresponding, dedicated console to handle the management operations of the associated network device. A further drawback is that the interface card of each network device in the chassis must maintain a dedicated connection to its corresponding console. Such a configuration of consoles and network devices adds costs and complexities to the management operations of communication systems.

15

SUMMARY OF THE INVENTION

In accordance with the present invention, the disadvantages and problems associated with prior management systems have been substantially reduced or eliminated.

5 In accordance with one embodiment of the present invention, a management system includes a first interface card, a second interface card, and a management card coupled to the first interface card and the second interface card. The management card establishes a
10 communication link between a client and a particular one of the first interface card and the second interface card selected in response to a command communicated by the client. The management card further communicates management information using the communication link.

15 Another embodiment of the present invention is a method for communicating management information that is performed by a management card. The method includes receiving a command from a client, the command identifying a particular one of the first interface card and a second
20 interface card. The method continues by establishing a communication link between the client and the particular interface card in response to receiving the command. The method concludes by communicating management information to the particular interface card using the communication link.

25 Yet another embodiment of the present invention is a management card that includes a switch coupled to a first interface card and a second interface card. A processor coupled to the switch receives a command communicated by the client. The command identifies a particular one of the
30 first interface card and the second interface card. The processor further commands the switch to establish the communication link between the client and the particular interface card.

Technical advantages of the present invention include a management card that establishes a communication link between a client and a particular one of a number of interface cards in response to a command communicated by the client, and communicates management information to the particular interface card using the established communication link. In this respect, one client may manage many interface cards and/or their associated network devices using the management card of the present invention. The configuration and operation of components in the present invention ameliorates a problem with prior management systems that require each network device to maintain a dedicated communication link to a dedicated client in a one-to-one configuration. The present invention therefore results in decreased costs and complexity in managing network devices.

Other technical advantages are readily apparent to one skilled in the art from the following figures, descriptions and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and its advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features and wherein:

FIGURE 1 illustrates a system for communicating management information according to the present invention;

FIGURE 2 illustrates one embodiment of a management card used by the system;

FIGURE 3 illustrates one embodiment of a mapping table used by the system; and

FIGURE 4 illustrates a flowchart of an exemplary method for communicating management information according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 illustrates a management system 10 that includes a management card 12 coupled to a number of interface cards 14 using links 16 and coupled to a client 18 using a link 20. In general, client 18 handles the primary management responsibilities for each of interface cards 14 and/or associated network devices 24 using management card 12.

Management card 12 comprises any suitable combination of hardware and software components that establish one or more communication links 22 between client 18 and one or more interface cards 14 selected in response to a command 40, and communicate management information 42 to the interface cards 14 using communication links 22. Although management card 12 is illustrated separate from interface cards 14, it should be understood that management card 12 may be formed integral to or separate from a particular interface card 14. Management card 12 is described in greater detail with respect to FIGURE 2.

Although the following description of system 10 is detailed with reference to establishing a communication link 22 between a client 18 and a particular one of interface cards 14, it should be understood that management card 12 may establish and maintain communication links 22 between a client 18 and any number and combination of interface cards 14. A communication link 22 comprises any switched communication path that couples client 18 to an interface card 14 and communicates management information 42 using any suitable communication protocols, standards, and/or formats.

Command 40 comprises information selecting one or more of interface cards 14 and/or network devices 24 to which management information 42 is directed. Although the following description of system 10 is detailed with respect to a command 40 comprising information selecting particular interface cards 14, it should be understood that

command 40 may also comprise information selecting particular network devices 24.

Management information 42 comprises information communicated to interface cards 14, such as configuration information, status information, addressing information, initialization information, management information base (MIB) variables, commands, requests, firmware patches, software files, or any other suitable arrangement of information used to manage the operation of an interface card 14 and/or associated network device 24. Management information 42 may further comprise information communicated to client 18 by an interface card 14, such as, for example, in response to a request.

Each interface card 14 comprises any suitable combination of hardware and software components that enable network devices 24 to communicate with various components of a communication network (not explicitly shown) and with other components of system 10. For example, interface cards 14 include management ports 26 that couple network devices 24 to management card 12 using links 16 such that devices 24 may communicate with management card 12. Network devices 24 comprise computers, servers, workstations, IP telephones, routers, bridges, switches, gateways, hubs, and any other suitable electronic devices that may be managed by client 18 using management card 12.

Links 16 comprise any suitable communication paths between management card 12 and interface cards 14. In a particular embodiment, links 16 comprise serial communication paths that support the RS-232 communication standards. The RS-232 communication standards cover the mechanical and signal interface between components of system 10 employing serial binary data interchange. Management card 12, interface cards 14, and network devices 24 generally reside in a single housing, rack mount, or chassis 28 at a particular location in management system 10.

Client 18 comprises a computer, a workstation, a console, a terminal, or any other suitable processing device that supports the management operations of interface cards 14 and/or network devices 24. Client 18 may execute software associated with management card 12 to perform the management operations of system 10. In one embodiment, client 18 couples locally to management card 12 of chassis 28 using link 20. In another embodiment, client 18 couples remotely to management card 12 of chassis 28 using link 20 and a modem 30. Link 20 comprises any suitable communication path that couples management card 12 to client 18. In a particular embodiment, link 20 comprises a serial communication path that supports the RS-232 communication standards. Modem 30 comprises any suitable communication device that transmits and receives data in management system 10 using any suitable communication protocol, standard, and/or format associated with link 20.

In operation, a user operates client 18 to communicate a command 40 and management information 42 to management card 12. Management card 12 receives command 40 communicated by client 18 and establishes one or more communication links 22 between client 18 and particular interface cards 14 selected in response to command 40. Using communication links 22, management card 12 communicates to the particular interface cards 14, the management information 42 communicated by client 18.

A particular advantage of the present invention is that one client 18 may manage many network devices 24 using management card 12. In this respect, management system 10 provides centralized management services to many network devices 24 of a particular chassis 28 using a single point of entry, such as management card 12. The configuration and operation of components in system 10 ameliorates a problem with prior management systems that require each network device 24 to maintain a dedicated communication link to a dedicated client 18 in a one-to-one

configuration. System 10 therefore results in decreased costs and complexity in managing network devices 24.

FIGURE 2 illustrates management card 12 in more detail. Communication link 20 couples client 18 to interface 50. Interface 50 couples to a line driver 52, which in turn couples to a processor 54. Processor 54 manages the overall operation of management card 12 and couples to memory 56 and line driver 58. Line driver 58 couples to switch 60 at a first port 62. Links 16 couple to switch 50 at second ports 64.

Interface 50 comprises any suitable combination of hardware and software components that terminates communication link 20 in management card 12. In one embodiment, interface 50 comprises a serial port connection and link 20 comprises a serial communication path between client 18 and management card 12. In another embodiment, interface 50 supports a remote connection between client 18 and management card 12, established using modem 30.

Line driver 52 comprises any suitable combination of hardware and software components that convert information communicated using a communication format associated with link 20 and/or client 18 to a communication format associated with processor 54. For example, line driver 52 converts commands 40 and information 42 communicated by client 18 using link 20 in the RS-233 communication standards to any suitable format associated with processor 54, such as Transistor Transistor Logic (TTL).

Processor 54 comprises a central processing unit having any suitable general purpose data processing capabilities. Memory 56 comprises any suitable volatile or non-volatile memory device associated with processor 54. Memory 56 generally stores a number of files, lists, tables, or any other arrangement of information that support establishing communication links 22 and communicating management information 42 using communication links 22. For example, memory 56 stores program

associated with links 16, interface cards 14, and/or network devices 24. Switch 60 establishes one or more communication links 22 between the appropriate ports 62 and 64 to couple client 18 to the appropriate interface cards 14. Management card 12 communicates management information 42 using communication link 22. In particular, management card 12 may communicate management information 42 from client 18 to interface cards 14 and/or may communicate management information 42 from interface cards 14 to client 18 such as, for example, in response to a request.

A particular operation performed by management card 12 to support the management of network devices 24 involves processor 54 populating the contents of mapping table 72. Upon receiving a command 40, an event time-out, or the occurrence of any other suitable trigger, processor 54 polls network devices 24 and/or interface cards 14 to determine the appropriate associations between device identifiers 80, operating system identifiers 82, and port identifiers 84 of mapping table 72. For example, processor 54 may poll the particular network device 24 and/or interface card 14 coupled to a particular port 64 of switch 60 to determine the associated identifiers 80 and 82. Processor 54 populates mapping table 72 according to the results of its polling operation.

FIGURE 4 illustrates a flowchart of an exemplary method for communicating management information 42 performed by management card 12 according to the present invention. The method begins at steps 100 and 102 where management card 12 receives a command 40 and management information 42 from client 18. Processor 54 of management card 12 identifies the interface cards 14 and/or network devices 24 to which management information 42 is directed using command 40 at step 104. At step 106, processor 54 determines the appropriate ports 64 of switch 60 associated with the particular interface cards 14 and/or network

devices 24 identified at step 104, using the information stored in mapping table 72.

At step 108, switch 60 of management card 12 establishes one or more communication links 22 between port 62 and the ports 64 determined at step 106. In this respect, switch 60 couples client 18 to the appropriate interface cards 14 and/or network devices 24. Processor 54 and/or line driver 58 configure management information 42 at step 110 using the information stored in mapping table 72. For example, processor 54 configures management information 42 according to the operating systems associated with the network devices 24 identified at step 104. In another example, line driver 58 configures management information 42 according to the communication format of links 16. Management card 12 communicates management information 42 at step 112. In particular, management card 12 may communicate management information 42 from client 18 to interface cards 14 and/or may communicate management information 42 from interface cards 14 to client 18 such as, for example, in response to a request. Execution terminates at step 114.

Although the present invention has been described in several embodiments, a myriad of changes, variations, alterations, transformations, and modifications may be suggested to one skilled in the art, and it is intended that the present invention encompass such changes, variations, alterations, transformations, and modifications as fall within the spirit and scope of the appended claims.

WHAT IS CLAIMED IS:

1. A system for communicating management information, comprising:

- 5 a first interface card;
a second interface card; and
a management card coupled to the first interface card and the second interface card, the management card operable to:

10 establish a communication link between a client and a particular one of the first interface card and the second interface card selected in response to a command communicated by the client; and

communicate management information using the communication link.

15 2. The system of Claim 1, wherein the management card comprises:

20 a switch operable to establish the communication link between the client and one of a first port and a second port;

a memory operable to store mapping information associating the first port with the first interface card and the second port with the second interface card; and

25 a processor coupled to the memory and the switch, the processor operable to:

receive the command identifying a particular interface card;

determine the port associated with the particular interface card using the mapping information; and

30 command the switch to establish the communication link between the client and the determined port.

3. The system of Claim 2, wherein:

the first interface card is coupled to a first network device that uses a first operating system;

5 the second interface card is coupled to a second network device that uses a second operating system; and

the processor is further operable to configure the management information for the operating system of the network device associated with the particular interface card.

10

4. The system of Claim 1, wherein the communication link comprises a serial communication path.

15

5. The system of Claim 1, wherein the command comprises information selecting one of the first interface card and the second interface card.

20

6. The system of Claim 1, wherein the management information comprises information used to configure a network device associated with the particular interface card.

7. A method for communicating management information performed by a management card, comprising:

receiving a command from a client, the command identifying a particular one of a first interface card and a second interface card;

establishing a communication link between the client and the particular interface card in response to receiving the command; and

communicating management information using the communication link.

8. The method of Claim 7, further comprising storing mapping information that associates a first port of a switch with the first interface card and a second port of the switch with the second interface card, the step of establishing a communication link comprising determining the port associated with the particular interface card using the mapping information and establishing the communication link between the client and the determined port using the switch.

9. The method of Claim 7, wherein:

the first interface card is coupled to a first network device that uses a first operating system;

the second interface card is coupled to a second network device that uses a second operating system; and

further comprising configuring the management information for the operating system of the network device associated with the particular interface card.

10. The method of Claim 7, further comprising operating the client to generate the command and the management information.

11. The method of Claim 7, wherein the communication link comprises a serial communication path.

12. The method of Claim 7, wherein the command comprises information selecting one of the first interface card and the second interface card.

5

13. The method of Claim 7, wherein the management information comprises information used to configure a network device associated with the particular interface card.

062891.0320

14. A management card, comprising:

a switch coupled to a first interface card and a second interface card; and

a processor coupled to the switch and operable to:

receive a command communicated by the client, the command identifying a particular one of the first interface card and the second interface card; and

command the switch to establish the communication link between the client and the particular interface card.

15. The management card of Claim 14, wherein:

the switch comprises a first port coupled to the first interface card and a second port coupled to the second interface card, the switch operable to establish the communication link between a client and one of the first port and the second port;

the management card further comprises a memory coupled to the processor and operable to store mapping information that associates the first port with the first interface card and the second port with the second interface card; and

the processor is further operable to:

determine the port associated with the particular interface card using the mapping information; and

command the switch to establish the communication link between the client and the determined port.

16. The management card of Claim 14, wherein the processor is further operable to communicate management information using the communication link.

17. The management card of Claim 14, wherein:
the first interface card is coupled to a first network
device that uses a first operating system;

5 the second interface card is coupled to a second
network device that uses a second operating system; and

the processor is further operable to configure the
management information for the operating system of the
network device associated with the particular interface
card.

10

18. The management card of Claim 14, wherein the
communication link comprises a serial communication path.

19. The management card of Claim 14, wherein the
15 command comprises information selecting one of the first
interface card and the second interface card.

20. The management card of Claim 14, wherein the
management information comprises information used to
20 configure a network device associated with the particular
interface card.

SYSTEM FOR COMMUNICATING MANAGEMENT
INFORMATION AND METHOD OF OPERATION

ABSTRACT OF THE DISCLOSURE

5 A system for communicating management information includes a first interface card, a second interface card, and a management card coupled to the first interface card and the second interface card. The management card establishes a communication link between a client and a particular one of the first interface card and the second interface card selected in response to a command communicated by the client. The management card further
10 communicates management information using the communication link.






FIG. 2

72

FIG. 3

80	82	84
DEVICE ID	OPERATING SYSTEM ID	PORT ID
ROUTER 1	RTOS	1
ROUTER 2	IOS	2
ROUTER 2 CARD	IOS	3
⋮	⋮	⋮
GATEWAY CARD	WINDOWS NT	n
FAULT MANAGEMENT CARD	-	n+1



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; that I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention or design entitled SYSTEM FOR COMMUNICATING MANAGEMENT INFORMATION AND METHOD OF OPERATION the specification of which is attached hereto; that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above; and that I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Number</u>	<u>Country</u>	<u>Date Filed</u>	<u>Priority Claimed (Yes) (No)</u>
---------------	----------------	-----------------------	--

-----NONE-----

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56 which became available between the

filing date of the prior application(s) and the national or PCT international filing date of this application:

<u>Application</u> <u>Serial Number</u>	<u>Date Filed</u>	<u>Status</u>
-----NONE-----		

I hereby appoint:

Jerry W. Mills	Reg. No. 23,005
Robert M. Chiaviello, Jr.	Reg. No. 32,461
Samir A. Bhavsar	Reg. No. 41,617
James L. Baudino	Reg. No. 43,486
Thomas R. Felger	Reg. No. 28,842
Charles S. Fish	Reg. No. 35,870
Robert W. Holland	Reg. No. 40,020
Wei Wei Jeang	Reg. No. 33,305
Jay B. Johnson	Reg. No. 38,193
Christopher W. Kennerly	Reg. No. 40,675
Tara D. Knapp	Reg. No. 43,723
Douglas M. Kubehl	Reg. No. 41,915
Ann C. Livingston	Reg. No. 32,479
Kevin J. Meek	Reg. No. 33,738
Harold E. Meier	Reg. No. 22,428
Randall W. Mishler	Reg. No. 42,006
Scott T. Morris	Reg. No. 43,818
Barton E. Showalter	Reg. No. 38,302
T. Murray Smith	Reg. No. 30,222
Terry J. Stalford	Reg. No. 39,522
David G. Wille	Reg. No. 38,363
Bradley P. Williams	Reg. No. 40,227
Rodger L. Tate	Reg. No. 27,399
Scott F. Partridge	Reg. No. 28,142
James B. Arpin	Reg. No. 33,470
James Remenick	Reg. No. 36,902
Roger J. Fulghum	Reg. No. 39,678
Thomas R. Nesbitt, Jr.	Reg. No. 22,075
James J. Maune	Reg. No. 26,946

all of the firm of Baker & Botts, L.L.P., my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, and to file and prosecute any international patent applications filed thereon before any international authorities under the Patent Cooperation Treaty.

Send Correspondence To:

Baker & Botts, L.L.P.
2001 Ross Avenue
Dallas, Texas 75201-2980

Direct Telephone Calls To:

Samir A. Bhavsar
at (214) 953-6418
Attorney Docket No. 062891.0320

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of first inventor

Shriniwas (nmi) Lohia

Inventor's signature

Shriniwas Lohia

Date

04 November 1999

Residence (City, County, State)

Fremont, Alameda County,
California

Citizenship

United States of America

Post Office Address

104 Concho Drive
Fremont, California 94539